



Bearing No	Dimensions(mm)					Load Rating(KN)		Weight (kg)
	d	D	B	r <sub>min</sub>	r <sub>1min</sub>	Dynamic Cr	Static Cor	
6403	17	62	17	1.1	0.5	22.5	10.8	0.268
6404	20	72	19	1.1	0.5	31	15.2	0.4
6405	25	80	21	1.5	0.5	38.2	19.2	0.529
6406	30	90	23	1.5	0.5	47.5	24.5	0.71
6407	35	100	25	1.5	0.5	56.8	29.5	0.926
6408	40	110	27	2	0.5	65.5	37.5	1.221
6409	45	120	29	2	0.5	77.5	45.5	1.521
6410	50	130	31	2.1	0.5	92.2	55.2	1.855
6411	55	140	33	2.1	0.5	100.6	62.5	2.316
6412	60	150	35	2.1	0.5	109.1	70	2.811
6413	65	160	37	2.1	0.5	118.14	78.57	3.342
6414	70	180	42	3	0.5	139.5	99.56	4.896
6415	75	190	45	3	0.5	153.78	114.32	5.739
6416	80	200	48	3	0.5	163.22	124.55	6.752
6417	85	210	52	4	/	174.9	137.49	7.933
6418	90	225	54	4	/	192.48	157.63	9.565
6419	95	240	55	4	/	206	171	11.2
6420	100	250	58	4	/	223.08	194.61	12.904