



Bearing Designations		Boundary Dimensions(mm)			Base Load Rating(KN)		Limting Speed(r/min)		weight (kg)
new standard	old standard	d	D	B	cr	cor	Grease	oil	
61900	1000900	10	22	6	2.7	1.3	25000	32000	0.008
61901	1000901	12	24	/	2.9	1.5	22000	28000	0.008
61902	1000902	15	28	/	4.3	2.3	20000	26000	0.012
61903	1000903	17	30	/	4.6	2.6	19000	24000	0.014
6190	1000904	20	37	/	6.4	3.7	17000	22000	0.031
61905	1000905	25	42	/	7	4.5	14000	18000	0.038
61906	1000906	30	47	9	7.2	5	12000	16000	0.043
61907	1000907	35	55	10	9.5	6.8	10000	13000	0.078
61908	1000908	40	62	12	13.7	9.9	9500	12000	0.103
61909	1000909	45	68	12	14.1	10.9	8500	11000	0.123
61910	1000910	50	72	12	14.5	11.7	8000	9500	0.132
6191	1000911	55	80	13	15.9	13.2	7500	9000	0.17
61912	1000912	60	85	13	16.4	14.2	6700	8000	0.181
61913	1000913	65	90	13	17.4	16	6300	7500	0.196
61914	1000914	70	100	16	23.7	21.1	6000	7000	0.336
61915	1000915	75	105	16	24.3	22.5	5600	6700	0.355
61916	1000916	80	110	16	24.9	23.9	5300	6300	0.375
61917	1000917	85	120	18	31.9	29.7	4800	6000	0.507
61918	1000918	90	125	18	32.8	31.5	4500	5600	0.533
61919	1000919	95	130	18	33.7	33.3	4300	5300	0.56



Thin-wall deep groove ball bearings 619 series

61920	1000920	100	140	20	42.7	41.9	4000	5000	0.77
61921	1000921	105	145	20	67	99	1783	2000	0.805
61922	1000922	110	150	20	43.6	44.4	3600	4500	0.84
61924	1000924	120	165	22	55	56.9	3200	4000	1.13
61926	1000926	130	180	24	65.1	67.2	3000	3800	1.496
61928	1000928	140	190	24	66.6	71.2	2800	3600	1.589
61930	1000930	150	210	28	84.7	90.2	2600	3200	2.454
61932	1000932	160	220	28	86.9	95.5	2400	3000	2.589
61934	1000934	170	230	28	88.8	100	2000	2800	2.725
61936	1000936	180	250	33	118	133	1900	2600	4.062