



Bearing Designations	Boundary Dimensions(mm)			Basic Load Rating(KN)		Limiting Speed(rtmin)		Wight (kg)
	d	D	B	cor	cr	oil	Grease	
71800	10	19	5	1.8	1.1	75000	120000	0.005
71801	12	21	5	2	1.4	70000	110000	0.006
71802	15	24	5	2.2	1.8	60000	90000	0.007
71803	17	26	5	2.3	1.9	53000	80000	0.008
71804	20	32	5	3.9	3.4	45000	67000	0.018
71805	25	37	5	4.2	4.1	38000	56000	0.022
71806	30	42	7	4.4	4.8	32000	48000	0.025
71807	35	47	7	4.6	5.5	26000	40000	0.029
71808	40	52	7	4.8	6.2	24000	38000	0.032
71809	45	58	7	4.9	6.7	20000	34000	0.04
71810	50	65	7	7.4	10	18000	30000	0.052
71811	55	72	7	0.2	13.8	16000	26000	0.081
71812	60	78	10	3.4	18	15000	24000	0.1
71813	65	85	10	3.4	18.8	14000	22000	0.125
71814	70	90	10	3.8	20	13000	20000	0.133
71815	75	95	10	14.2	21.7	12000	19000	0.142
71816	80	100	10	4.5	23.1	10000	18000	0.15
71817	85	110	13	21.5	32.2	10000	17000	0.262
71818	90	115	13	21.7	33.5	9500	16000	0.274
71819	95	120	13	21.9	34.7	9000	15000	0.287



Thin-wall angular contact ball bearings 718 series

71820	100	25	13	22.5	37	8500	14000	0.301
71821	105	130	13	22.7	38.3	8500	14000	0.314
71822	110	140	16	31.8	51.6	8000	13000	0.496