



Bearing No.	Dimensions (mm)							Dynamic Load Rating (K N)	Rated Static Load (K N)	Weight (kg)
	d	D	B	C	T	Rmin	rmin			
30203	17	40	12	11	13.25	1	1	20.7	21.9	0.079
30204	20	47	14	12	15.25	1	1	28.2	30.6	0.126
30205	25	52	15	13	16.25	1	1	32.2	37	0.154
30206	30	62	16	14	17.25	1	1	43.3	50.5	0.231
30207	35	72	17	15	18.25	1.5	1.5	54.2	63.5	0.331
30208	40	80	18	16	9.7C	1.5	1.5	63	74	0.422
30209	45	85	19	16	20.75	1.5	1.5	67.9	83.6	0.474
30210	50	90	20	17	21.76	1.5	1.5	73.3	92.1	0.529
30211	55	100	21	18	22.75	1.5	1.5	90.8	113.7	0.713
30212	60	110	22	19	23.75	1.5	1.5	103.3	130	0.904
30213	65	120	23	20	24.75	1.5	1.5	120.6	152.6	1.13
30214	70	125	24	21	26.21	1.5	1.5	132.3	173.6	1.26
30215	75	130	25	22	27.25	1.5	1.5	138.4	185.4	1.36
30216	80	140	26	22	28.25	2.5	2	160.4	212.8	1.67
30217	85	150	28	24	30.5	2.5	2	177.6	236.8	2.06
30218	90	160	30	26	32.5	2.5	2	200.1	269.6	2.54
30219	95	170	32	27	34	3	2.5	226.6	309	3.04
30220	100	180	34	29	37	3	2.5	253.9	350.3	3.72
30221	105	190	36	30	39	3	2.5	285.3	398.6	4.38
30222	110	200	38	32	41	3	2.5	314.9	443.6	5.21



30 series

30303	17	47	14	12	5.25	1	1	28.3	27.2	0.12C
30304	20	52	15	13	6.2	1.5	1.5	33.1	33.2	0.165
30305	25	62	17	15	8.25	1.5	1.5	46.9	48.1	0.263
30306	30	72	19	16	20.75	1.5	1.5	59.0	63.1	0.387
30307	35	80	21	18	22.75	2	1.5	75.3	82.6	0.515
30308	40	90	23	20	25.25	2	1.5	90.9	107.6	0.747
30309	45	100	25	22	27.25	2	1.5	108.9	129.8	0.984
27709K	45	100	29	20.5	32	2.5	2.5	101.1	110.8	1.081
30310	50	110	27	23	29.25	2.5	130.1	157.1	157.1	1.28
30311	55	120	29	25	31.5	2.5	153.3	187.6	187.6	1.63