



Bearing No.	Dimensions (mm)					Dynamic Load Rating (K N)		Rated Static Load (K N)	Weight (kg)	
	d	D	B	C	T	Rmin	rmin			
32004X	20	42	15	12	15	0.6	0.6	25.1	28.2	0.095
32005X	25	47	15	11.5	15	0.6	0.6	28	34.1	0.112
32006X	30	55	17	13	17	1	1	35.7	46.8	0.17
32007X	35	62	18	14	18	1	1	43.2	59.2	0.224
32008X	40	68	19	14.5	19	1	1	51.9	71.1	0.269
32009	45	75	20	15.5	20	1	1	58.4	81.4	0.337
32010X	20	80	20	15.5	20	1	1	61.1	89	0.366
32011	55	90	23	17.5	23	1.5	1.5	80.2	117.2	0.551
32012	60	95	23	17.5	23	1.5	1.5	81.7	122.2	0.584
32013	65	100	23	17.5	23	1.5	1.5	82.8	127.3	0.62
32014	70	110	25	19	25	1.5	1.5	104.3	160.1	0.839
32015	75	115	25	19	25	1.5	1.5	103.1	160.2	0.875
32016	80	125	29	22	29	2.5	1.5	140	220	1.27
32017	85	130	29	22	29	2.5	1.5	140	220	1.32
32018	90	140	32	24	32	2	1.5	170	270	1.72
32019	95	145	32	24	32	2	1.5	185	280	1.84
32020	100	150	32	24	32	2	1.5	192	282	1.85
32021	105	160	35	26	35	2.5	2	205	335	2.4
32022	110	170	38	29	38	2.5	2	245	402	3.02
32024	120	180	38	29	38	2.5	2	242	405	3.18



32 series

32026	130	200	45	34	45	3	2.5	335	568	4.94
32028	140	210	45	34	45	3	2.5	330	568	5.15
32030	150	225	18.5	36	48.5	3	2.5	368	635	6.25
32205	25	52	18	16	19.25	1	1	41.3	49.2	0.199
32206	30	62	20	17	21.25	1	1	51.8	63.7	0.287
32207	35	72	23	19	24.25	1.5	1.5	70.6	895	0.445
32208	40	80	23	19	24.75	1.5	1.5	77.9	97.2	0.532
32209	45	85	23	19	24.75	1.5	1.5	80.7	104	0.573
32210	50	90	23	19	24.75	1.5	1.5	82.8	107.6	0.626
32211	55	100	25	21	26.75	2	1.5	108	142.3	0.853