



Bearing No.	Dimensions (mm)					Dynamic Load		Rated Static	Weight (kg)	
	d	D	B	C	T	Rmin	rmin	Rating (K N)		Load (K N)
33108	40	75	26	20.5	26	2	1.5	84.8	110	0.496
33109	45	80	26	20.5	26	2	1.5	87	118	0.535
33110	50	85	26	20	26	2	1.5	89.2	125	0.572
33111	55	90	30	23	30	2	1.5	115	165	0.843
33112	60	100	30	23	30	2	1.5	118	172	0.985
33113	65	110	34	26.5	34	2	1.5	142	220	1.3
33114	70	120	37	29	37	2	1.5	172	268	1.7
33115	75	125	37	29	37	2	1.5	175	280	1.78
33116	80	130	37	29	37	2	1.5	180	292	1.87
33117	85	140	41	32	41	2	1.5	215	355	2.43
33118	90	150	45	35	45	2.5	2	252	415	3.13
33119	95	160	49	38	49	2.5	2	298	498	3.49
33120	100	165	52	40	52	2.5	2	325	523	4.31
33205	25	52	22	18	22	1	1	47.1	55.8	0.216
33205/Q	25	52	22	18	22	1	1.3	47.3	59.5	0.22
332/28	28	58	24	19	24	1	1	58	68.3	0.286
33206	30	62	25	19.5	25	1	1	63.8	75.4	0.342
332/32	32	65	26	20.5	26	1	1	68.8	82.2	0.385
33207	35	72	28	22	28	1.5	1.5	82.6	101.7	0.515
33208	40	80	32	25	32	1.5	1.5	105.8	135.5	0.715
33209	45	85	32	25	32	1.5	1.5	109.5	145.1	0.771



33 series

33210	50	90	32	24.5	32	1.5	1.5	112.9	1546	0.825
33211	55	100	35	27	35	2	1.5	143.1	196.7	1.15
33212	60	110	38	29	38	2	1.5	165.8	231.4	1.51
33213	65	120	41	32	41	2	1.5	202.2	281.6	1.99
33214	70	125	41	32	41	2	1.5	208.6	298.3	2.1
33215	75	130	41	31	41	2	1.5	207.1	299.7	2.17
33216	80	140	46	35	46	2.5	2	245.7	361.8	2.83
33216X2	80	140	45	36.5	45	2.5	2.5	226.6	348.5	2.775