



Polyurethane molded bearing + stainless steel external thread

serial number	bearing No.	Lagging size			Built-in bearing	Screw size			Replacement of Misumi code name
		Inner diameter mm	Outer diameter mm	Thickness mm		Step protruding C	Screw length L	Thread M	
1	MR63-7-3C1L4M2	/	7	2.5	MR63	/	/	/	/
2	683-10-3C1L4M3	/	10	3	683	/	/	/	UMBH3-10
3	683-10-3C1L ⁶ M3	3	10	3	683	/	6	3	UMBT3-10
4	693-10-4C1L5M4	3	10	4	693	/	5	4	/
5	684-11-4C1L5M4	4	11	4	684	/	5	4	/
6	684-11-4C1.5L5M4	4	11	4	684	1.5	5	4	/
7	684-11-4C1L8M4	4	11	4	684	/	8	4	/
8	683-12-3C1L4M3	3	12	3	683	1	4	3	UMBH3-12
9	683-12-3C1L6M3	3	12	3	683	/	6	3	UMBT3-12
10	684-13-4C1L5M4	4	13	4	684	/	5	4	UMBH4-13
11	684-13-4C1.5L5M4	4	13	4	684	1.5	5	4	/
12	684-13-4C1L8M4	4	13	4	684	/	8	4	UMBT4-13
13	685-14-5C1L5M4	5	14	5	685	/	5	4	/
14	685-14-5C1L6M4	5	14	5	685	1	6	4	/
15	685-14-5C1.5L6M4	5	14	5	685	1.5	6	4	/
16	685-14-5C1L8M4	5	14	5	685	/	8	4	/
17	685-14-5C2L6M5	5	14	5	685	2	6	5	/
18	685-14-5C2L8M6	5	14	5	685	2	8	6	/
19	685-14-5C3L8M6	5	14	5	685	3	8	6	/
20	685-14-5C2L10M5	5	14	5	685	2	10	5	/
21	623-15-4C1L5M4	3	15	4	623	/	5	4	/



Polyurethane molded bearing + stainless steel external thread

22	623-15-4C1.5L4M3	3	15	4	623	1.5	4	3	/
23	623-15-4C1.5L6M3	3	15	4	623	1.5	6	3	/
24	624-15-5C1L5M4	4	15	5	624	/	5	/	/
25	624-15-5C1L6M4	4	15	5	624	/	6	4	/
26	624-15-5C1L8M4	4	15	5	624	1	8	4	/
27	624-16-5C1L5M4	/	16	5	624	/	5	/	UMBH4-16
28	624-16-5C1L6M4	4	16	5	624	/	6	4	/
29	624-16-5C1L8M4	4	16	5	624	/	8	4	UMBT4-16
30	685-16-5C1L5M4	5	16	5	685	1	5	4	UMBH5-16