



Polyurethane molded bearing R-shaped arc type + stainless steel external thread



Polyurethane molded bearing + stainless steel external thread

serial number	bearing No.	Lagging size			Built-in bearing	Screw size			Replacement of Misumi code name
		Inner diameter mm	Outer diameter mm	Thickness mm		Step protruding length C	Screw length L	Thread M	
1	R683-12-3C1L4M3	3	12	3	683	1	4	3	UMBRH3-12
2	R683-12-3C1L6M3	3	12	/	683	/	6	3	UMBRT3-12
3	R684-13-4C1L5M4	4	13	4	684	/	5	4	UMBRH4-13
4	R684-13-4C1L8M4	4	13	4	684	1	8	4	UMBRT4-13
5	R624-16-5C1L5M4	/	16	5	624	/	5	/	UMBRH4-16
6	R624-16-5C1L6M4	/	16	5	624	/	6	/	/
7	R624-16-5C1L8M4	4	16	5	624	1	8	4	UMBRT4-16
8	R685-16-5C1L5M4	5	16	5	685	/	5	4	UMBRH5-16
9	R685-16-5C1L6M4	5	16	5	685	/	6	4	/
10	R685-16-5C1L8M4	5	16	5	685	1	8	4	UMBRT5-16
11	R685-16-5C2L6M5	5	16	5	685	2	6	5	/
12	R685-16-5C2L8M6	5	16	5	685	/	8	6	/
13	R685-16-5C3L8M6	5	16	5	685	3	8	6	/
14	R685-16-5C2L10M5	5	16	5	685	2	10	5	/
15	R625-20-5C1L5M4	5	20	5	625	/	5	/	UMBRH5-20
16	R625-20-5C1L6M4	5	20	5	625	1	6	4	/
17	R625-20-5C1L8M4	5	20	5	625	/	8	/	UMBRT5-20
18	R625-20-5C2L6M5	5	20	5	625	2	6	5	/
19	R625-20-5C2L8M6	5	20	5	625	2	8	6	/
20	R625-20-5C3L8M6	5	20	5	625	3	8	6	/
21	R625-20-5C2L10M5	5	20	5	625	2	10	5	/
22	R696-20-5C1L4M6	6	20	5	696	1	4	6	/



Polyurethane molded bearing R-shaped arc type + stainless steel

			external thread						
23	R696-20-5C1L8M6	6	20	5	696	/	8	6	UMBRH6-20
24	R696-20-5C1.5L8M6	6	20	5	696	1.5	8	6	/
25	R696-20-5C2L8M6	6	20	5	696	2	8	6	/
26	R696-20-5C2.5L8M6	6	20	5	696	2.5	8	6	/
27	R696-20-5C3L8M6	6	20	5	696	3	8	6	/
28	R696-20-5C6L8M6	6	20	5	696	6	8	6	/
29	R696-20-5C1L12M6	6	20	5	696	/	12	6	UMBRT6-20
30	R696-20-5C1.5L12M6	6	20	5	696	1.5	12	6	/