



Silicone molded bearing + stainless steel external thread

serial number	bearing No.	Lagging size			Built-in bearing	Screw size			Replacement of Misumi code name
		Inner diameter mm	Outer diameter mm	Thickness mm		Step protruding C	Screw length L	Thread M	
/	683-12-3C1L4M3	/	12	/	683	1	4	3	SUMBH3-12
2	683-12-3C2L4M3	/	12	3	683	2	4	3	/
3	683-12-3C1L6M3	3	12	3	683	/	6	3	SUMBT3-12
4	684-13-4C1L5M4	4	13	4	684	/	5	4	SU MBH4-13
5	684-13-4C1L8M4	4	13	4	684	/	8	4	SUMBT4-13
6	624-16-5C1L5M4	4	16	5	624	/	5	/	SUMBH4-16
7	624-16-5C1L6M4	/	16	/	624	/	6	4	/
8	624-16-5C1L8M4	4	16	5	624	1	8	4	SUMBT4-16
9	685-16-5C1L5M4	5	16	5	685	/	5	/	SUMBH5-16
10	685-16-5C1L6M4	/	16	/	685	/	6	4	/
11	685-16-5C2L6M5	/	16	/	685	2	6	5	/
12	685-16-5-C1L8M4	5	16	5	685	1	8	4	SUMBT5-16
13	685-16-5C2L8M6	/	16	5	685	2	8	6	/
14	685-16-5C3L8M6	5	16	5	685	3	8	6	/
15	685-16-502L10M5	5	16	5	685	2	10	5	/
16	625-20-5C1L5M4	5	20	5	625	1	5	4	SUMBH5-20
17	625-20-5C1L6M4	5	20	5	625	/	6	4	/
18	625-20-5C2L6M5	/	20	5	625	2	6	5	/
19	625-20-5C1L8M4	5	20	5	625	1	8	4	SUMBT5-20
20	625-20-5C2L8M6	5	20	5	625	2	8	6	/



Silicone molded bearing + stainless steel external thread

21	625-20-5C3L8M6	/	20	/	625	3	8	6	/
22	625-20-5C2L10M5	/	20	5	625	2	10	5	/
23	696-20-5C1L4M6	6	20	5	696	1	4	6	/
24	696-20-5C1L8M6	6	20	5	696	1	8	6	SUMBH6-20
25	696-20-5C2L8M6	6	20	5	696	2	8	6	/
26	696-20-5C3L8M6	6	20	5	696	3	8	6	/
27	696-20-5C6L8M6	6	20	5	696	6	8	6	/
28	696-20-5C1L12M6	6	20	5	696	/	12	6	SUMBT6-20
29	626-28-6C1L8M6	/	28	/	626	/	8	6	SUMBH6-28
30	626-28-6C2L8M6	6	28	6	626	2	8	6	/