



# Polyurethane stainless steel formed bearing + stainless steel external thread



**Polyurethane molded bearing + stainless steel external thread**

serial number	bearing No.	Lagging size			Built-in bearing	Screw size			Replacement of Misumi code name
		Inner diameter mm	Outer diameter mm	Thickness mm		Step protruding length C	Screw length L	Thread M	
1	S683-12-3C1L4M3	3	12	3	S683	/	4	3	UMSBH3-12
2	S683-12-3C1L6M3	3	12	3	S683	/	6	3	UMSBT3-12
3	S684-13-4C1L5M4	4	13	4	S684	/	5	4	UMSBH4-13
4	S684-13-4C1L8M4	4	13	4	S684	/	8	4	UMSBT4-13
5	S624-16-5C1L5M4	4	16	5	S624	1	5	4	UMSBH4-16
6	S624-16-5C1L6M4	4	16	5	S624	/	6	4	/
7	S624-16-5C1L8M4	/	16	5	S624	/	8	/	UMSBT4-16
8	S685-16-5C1L5M4	5	16	5	S685	/	5	4	UMSBH5-16
9	S685-16-5C1L6M4	5	16	5	S685	1	6	4	/
10	S685-16-5C1L8M4	5	16	5	S685	/	8	4	UMSBT5-16
11	S685-16-5C2L6M5	5	16	5	S685	/	6	/	/
12	S685-16-5C2L8M6	/	16	5	S685	2	8	6	/
13	S685-16-5C3L8M6	5	16	5	S685	3	8	6	/
14	S685-16-5C2L10M5	5	16	5	S685	2	10	5	/
15	S625-20-5C1L5M4	/	20	5	S625	/	5	4	UMSBH5-20
16	S625-20-5C1L6M4	5	20	5	S625	/	6	4	/
17	S625-20-5C1L8M4	5	20	5	S625	/	8	4	UMSBT5-20
18	S625-20-5C2L6M5	5	20	5	S62	2	6	5	/
19	S625-20-5C2L8M6	/	20	5	S625	/	8	6	/
20	S625-20-5C3L8M6	/	20	5	S625	3	8	6	/
21	S625-20-5C2L10M5	5	20	5	S625	2	10	5	/
22	S696-20-5C1L8M6	6	20	5	S696	/	8	6	UMSBH6-20



## Polyurethane stainless steel formed bearing + stainless steel external

				thread					
23	S696-20-5C1.5L8M6	6	20	5	S696	1.5	8	6	/
24	S696-20-5C2L8M6	6	20	5	S696	2	8	6	/
25	S696-20-5C3L8M6	6	20	5	S696	3	8	6	/
26	S696-20-5C6L8M6	6	20	5	S696	6	8	6	/
27	S696-20-5C1L12M6	6	20	5	S696	/	12	6	UMSBT6-20
28	S696-20-5C2.5L12M6	/	20	5	S696	2.5	12	/	/
29	S626-28-6C1L8M6	6	28	6	S626	/	8	6	UMSBH6-28
30	S626-28-6C2L8M6	6	28	6	S626	2	8	6	/