



Anti-static polyurethane + stainless steel external thread

serial number	bearing No.	Lagging size			Built-in bearing	Screw size			Replacement of Misumi code name
		Inner diameter mm	Outer diameter mm	Thickness mm		Step protruding length C	Screw length L	Thread M	
1	683-12-3C1L4M3	/	12	/	683	/	/	3	UMBDH3-12
2	683-12-3C1L6M3	/	12	3	683	/	6	3	UMBDT3-12
3	684-13-4C1L5M4	4	13	4	684	/	5	4	UMBDH4-13
4	684-13-4C1L8M4	4	13	4	684	/	8	4	UMBDT4-13
5	624-16-5C1L5M4	4	16	5	624	/	5	4	UMBDH4-16
6	624-16-5C1L6M4	/	16	5	624	/	6	4	/
7	624-16-5C1L8M4	/	16	5	624	/	8	4	UMBDT4-16
8	685-16-5C1L5M4	/	16	5	685	/	/	4	UMBDH5-16
9	685-16-5C1L6M4	5	16	5	685	/	6	4	/
10	685-16-5C1L8M4	5	16	5	685	/	8	4	UMBDT5-16
11	685-16-5C2L6M5	5	16	5	685	2	6	5	/
12	685-16-5C2L8M6	5	16	5	685	2	8	6	/
13	685-16-5C3L8M6	5	16	5	685	3	8	6	/
14	685-16-5C2L10M5	5	16	5	685	2	10	5	/
15	625-20-5C1L5M4	5	20	5	625	/	5	4	UMBDH5-20
16	625-20-5C1L6M4	5	20	5	625	/	6	4	/
17	625-20-5C1L8M4	5	20	5	625	/	8	4	UMBDT5-20
18	625-20-5C2L6M5	5	20	5	625	2	6	5	/
19	625-20-5C2L8M6	5	20	5	625	2	8	6	/
20	625-20-5C3L8M6	5	20	5	625	3	8	6	/
21	625-20-5C2L10M5	5	20	5	625	2	10	5	/



## Anti-static polyurethane + stainless steel external thread

22	696-20-5C1L4M6	6	20	5	696	/	4	6	/
23	696-20-5C1L8M6	6	20	5	696	/	8	6	UMBDH6-20
24	696-20-5C1.5L8M6	6	20	5	696	1.5	8	6	/
25	696-20-5C2L8M6	6	20	5	696	2	8	6	/
26	696-20-5C3L8M6	6	20	5	696	3	8	6	/
27	696-20-5C6L8M6	6	20	5	696	6	8	6	/
28	696-20-5C1L12M6	6	20	5	696	/	12	6	UMBDT6-20
29	696-20-5C2.5L12M6	6	20	5	696	2.5	12	6	/
30	626-28-6C1L8M6	6	28	6	626	/	8	6	UMBDH6-28