



**Polyurethane  
molded bearing +  
stainless steel  
external thread**

**Lagging size**

**Screw size**

**Replacement  
of Misumi  
code name**

serial number	bearing No.	Lagging size			Built-in bearing	Screw size		Thread M	Replacement of Misumi code name
		Inner diameter mm	Outer diameter mm	Thickness mm		Step protruding length C	Screw length L		
1	683-10-3	/	10	/	683	/	/	/	/
2	683-12-3	/	12	3	683	3	/	/	/
3	683-12-5	/	12	5	683	3	/	/	/
4	693-10-4	/	10	4	693	3	8	/	/
5	684-11-4	/	11	4	684	4	9	/	/
6	684-12-5	/	12	5	684	4	9	/	/
7	684-13-4	/	13	4	684	4	9	/	/
8	684-13-5	4	13	5	684	4	9	4	EB13
9	684-14-4	4	14	4	684	4	9	4	/
10	684-14-5	4	14	5	684	4	9	4	ER <sup>1</sup>
11	684-14-6	4	14	6	684	4	9	4	/
12	623-15-4	3	15	4	623	3	10	4	/
13	695-16-5	5	16	5	695	5	13	5	EB16
14	624-16-5	/	16	5	624	4	13	5	/
15	624-18-5	/	18	5	624	/	13	/	/
16	605-18-5	5	18	5	605	5	14	5	/
17	695-18-5	/	18	5	695	5	13	/	EB18
18	605-19-5	5	19	5	605	5	14	5	/
19	686-19-6	6	19	6	686	6	13	4	/



PA.POM plastic coated bearings

20	696-19-6	6	19	6	696	6	15	5	EB19
21	605-19-7	5	19	7	605	5	14	5	/
22	625-20-5	5	20	5	625	5	16	5	/
23	605-20-5	5	20	5	605	5	14	5	/
24	697-21-6.3	/	21	6.3	697	/	17	5	/
25	696-20-5	6	20	/	696	6	15	5	/
26	696-20-6	6	20	6	696	6	15	5	EB20
27	606-22-6	6	22	6	606	6	17	6	/
28	696-22-6	6	22	6	696	6	15	/	EB22
29	625-22-7	5	22	7	625	5	16	5	/
30	696-22.5-7	6	22.5	7	696	6	15	5	/