



PA POM plastic coated bearing + stainless steel external thread

serial number	bearing No.	Lagging size			Built-in bearing	Screw size			Replacement of Misumi code name
		Inner diameter mm	Outer diameter mm	Thickness mm		Step protruding length C	Screw length L	Thread M	
1	683-10-3C1L4M3	3	10	3	683	/	4	/	/
2	683-10-3C1L6M3	3	10	3	683	/	6	3	/
3	684-11-4C1L5M4	4	11	4	684	1	5	4	/
4	684-11-4C1.5L5M4	4	11	4	684	1.5	5	4	/
5	684-11-4C1L8M4	4	11	4	684	/	8	4	/
6	683-12-3C1L4M3	3	12	3	683	/	4	3	/
7	683-12-3C1L6M3	3	12	3	683	/	6	3	/
8	693-10-4C1L5M4	3	10	4	693	/	5	/	/
9	684-12-5C1L5M4	/	12	5	684	/	5	/	/
10	684-12-5C0.5L8M4	/	12	5	684	0.5	8	/	/
11	684-13-4C1L5M4	/	13	/	684	/	5	/	/
12	684-13-4C1.5L5M4	/	13	/	684	1.5	5	/	/
13	684-13-4C1L8M4	/	13	/	684	/	8	/	/
14	684-13-5C1L5M4	/	13	5	684	/	5	4	EBH13
15	684-13-5C0.5L8M4	4	13	5	684	0.5	8	4	/
16	684-14-5C1L5M4	4	14	5	684	/	5	4	EBH14
17	684-14-5C0.5L8M4	4	14	5	684	0.5	8	4	/
18	623-15-4C1L5M4	3	15	4	623	/	5	4	/
19	624-15-5C1L5M4	4	15	5	624	/	5	/	/
20	624-15-5C1L6M4	4	15	5	624	/	6	4	/
21	624-15-5C1L8M4	4	15	5	624	/	8	/	/



PA POM plastic coated bearing + stainless steel external thread

22	624-16-5C1L5M4	4	16	5	624	1	5	4	/
23	624-16-5C1L6M4	4	16	5	624	/	6	/	/
24	624-16-5C1L8M4	4	16	5	624	1	8	4	/
25	695-16-5C1L5M4	5	16	5	695	/	5	4	EBH16
26	695-16-5C1L6M4	5	16	5	695	/	6	4	/
27	695-16-5C1.5L6M4	5	16	5	695	1.5	6	4	/
28	695-16-5C1L8M4	5	16	5	695	/	8	/	/
29	695-16-5C2L6M5	5	16	5	695	2	6	5	/
30	695-16-5C2L8M6	5	16	5	695	2	8	6	/