



PA.POM plastic coated bearing R-type arc type + stainless steel external thread



PA.POM plastic coated bearing R-type arc type + stainless steel external thread

serial number	bearing No.	Lagging size			Built-in bearing	Screw size			R	Replacement of Misumi code name
		Inner diameter mm	Outer diameter mm	Thickness mm		Step protruding C	Screw length L	Thread M		
1	R696-19-6C1L8M6	/	19	6	696	/	8	6	5	ERBH19
2	R696-19-6C1.5L8M6	/	19	6	696	1.5	8	6	5	/
3	R696-19-6C2L8M6	/	19	6	696	2	8	6	5	/
4	R696-19-6C2.5L8M6	6	19	6	696	2.5	8	6	5	/
5	R696-19-6C5.5L8M6	6	19	6	696	5.5	8	6	5	/
6	R696-19-6C1L12M6	6	19	6	696	/	12	6	5	/
7	R696-20-6C1L8M6	/	20	6	696	/	8	6	5	ERBH20
8	R696-20-6C1.5L8M6	6	20	6	696	1.5	8	6	5	/
9	R696-20-6C2L8M6	6	20	6	696	2	8	6	5	/
10	R696-20-6C2.5L8M6	6	20	6	696	2.5	8	6	5	/
11	R696-20-6C5.5L8M6	6	20	6	696	5.5	8	6	5	/
12	R696-20-6C1L12M6	6	20	6	696	/	12	6	5	/
13	R696-22-6C1L8M6	6	22	6	696	1	8	6	5	ERBH22
14	R696-22-6C1.5L8M6	6	22	6	696	1.5	8	6	5	/
15	R696-22-6C2L8M6	6	22	6	696	2	8	6	5	/
16	R696-22-6C2.5L8M6	/	22	6	696	2.5	8	6	5	/
17	R696-22-6C5.5L8M6	6	22	6	696	5.5	8	6	5	/
18	R696-22-6C1L12M6	/	22	6	696	/	12	6	5	/
19	R688-22-7C1L6M6	8	22	7	688	1	6	6	5	/
20	R688-22-7C1L8M6	8	22	7	688	/	8	6	5	/
21	R626-22.35-7C1.5L8M6	6	22.35	7	626	1.5	8	6	15	/
22	R626-22.35-7C2L8M6	/	22.35	/	626	2	8	6	15	/
23	R626-22.35-7C2.5L8M6	6	22.35	7	626	2.5	8	6	15	/
24	R626-22.35-7C3.5L8M6	/	22.35	7	626	3.5	8	6	15	/



PA.POM plastic coated bearing R-type arc type + stainless steel external

				thread						
25	R626-22.35-7C4.5L8M6	6	22.35	7	626	4.5	8	6	15	/
26	R626-22.35-7C5.5L8M6	6	22.35	/	626	5.5	8	6	15	/
27	R626-22.35-7C4.5L10M6	6	22.35	7	626	4.5	10	6	15	/
28	R626-22.35-7C2L12M6	/	22.35	/	626	2	12	6	15	/
29	R626-22.35-7C2L15M6	6	22.35	7	626	2	15	6	15	/
30	R626-22.35-7C12.5L10M6	6	22.35	/	626	12.5	10	6	15	/