



Designation	Principal Dimensions(mm)				Basic Load Ratings(KN)		Limited Speed(rpm)		Weight (kg)
	d	D	B	rs min	Dynamic(Cr)	Static(Cor)	Grease	Oil	
24122	110	180	69	2	450	755	1500	2400	7.07
24122K30	110	180	69	2	450	755	1500	2400	6.96
24122K30W33C3	110	180	69	2	450	755	1500	2400	6.96
24122W33C3	110	180	69	2	450	755	1500	2400	7.07
24124	120	200	80	2	575	945	1400	2100	10.3
24124K30	120	200	80	2	575	945	1400	2100	10.1
24124K30W33C3	120	200	80	2	575	945	1400	2100	10.1
24124W33C3	120	200	80	2	575	945	1400	2100	10.3
24126	130	210	80	2	585	995	1300	2000	11
24126K30	130	210	80	2	585	995	1300	2000	10.8
24126K30W33C3	130	210	80	2	585	995	1300	2000	10.8
24126W33C3	130	210	80	2	585	995	1300	2000	11
24128	140	225	85	2.1	670	1150	1200	1800	13.3
24128K30	140	225	85	2.1	670	1150	1200	1800	13.1
24128K30W33C3	140	225	85	2.1	670	1150	1200	1800	13.1
24128W33C3	140	225	85	2.1	670	1150	1200	1800	13.3
24130	150	250	100	2.1	885	1520	1100	1700	20.2
24130K30	150	250	100	2.1	885	1520	1100	1700	20
24130K30W33C3	150	250	100	2.1	885	1520	1100	1700	20
24130W33C3	150	250	100	2.1	885	1520	1100	1700	20.2



24100 Series

24132	160	270	109	2.1	1040	1780	1000	1600	26
24132K30	160	270	109	2.1	1040	1780	1000	1600	25.6
24132K30W33C3	160	270	109	2.1	1040	1780	1000	1600	25.6
24132W33C3	160	270	109	2.1	1040	1780	1000	1600	26
24134	170	280	109	2.1	1080	1880	960	1500	27.2
24134K30	170	280	109	2.1	1080	1880	960	1500	26.8
24134K30W33C3	170	280	109	2.1	1080	1880	960	1500	26.8
24134W33C3	170	280	109	2.1	1080	1880	960	1500	27.2
24136	180	300	118	3	1250	2210	900	1400	34.3
24136K30	180	300	118	3	1250	2210	900	1400	33.8