



Bearing No		Main dimensions								Rated load(KN)		Weight(g)
No1	No2	D	C1	d1	G	G1	B	B1	B2	Dynamic load (C)	Static load (C)	
CF3	KR10	10	7	3	M3×0.5	5	8	17	9	1.18	1.47	4.5
CF4	KR12	12	8	4	M4×0.7	6	9	20	11	1.85	2.06	7.5
CF5	KR13	13	9	5	M5×0.8	7	10	23	13	2.77	3.14	10.5
CF6	KR16	16	11	6	M6×1.0	8	12.2	28.2	16	3.11	3.58	19
CF8	KR19	19	11	8	M8×1.25	10	12.2	32.2	20	4.17	4.65	29
CF10	KR22	22	12	10	M10×1.25	12	13.2	36.2	23	5.33	6.78	46
CF10-1	KR26	26	12	10	M10×1.25	12	13.2	36.2	23	5.33	6.78	61
CF12	KR30	30	14	12	M12×1.5	13	15.2	40.2	25	7.87	9.79	97
CF12-1	KR32	32	14	12	M12×1.5	13	15.2	40.2	25	7.87	9.79	107
CF16	KR35	35	18	16	M16×1.5	17	19.2	52.1	32.5	12	18.3	173
CF18	KR40	40	20	18	M18×1.5	19	21.6	58.1	36.5	14.7	25.2	255
CF20	KR52	52	24	20	M20×1.5	21	25.6	66.1	40.5	20.7	34.8	390
CF20-1	KR47	47	24	20	M20×1.5	21	25.6	66.1	40.5	20.7	34.8	465
CF24	KR62	62	29	24	M24×1.5	25	30.6	80.1	49.5	30.6	53.2	820
CF24-1	KR72	72	29	24	M24×1.5	25	30.6	80.1	49.5	30.6	53.2	1140
CF30	KR80	80	35	30	M30×1.5	32	37	100	63	45.4	87.6	1870
CF30-1	KR85	85	35	30	M30×1.5	32	37	100	63	45.4	87.6	2030
CF30-2	KR90	90	35	30	M30×1.5	32	37	100	63	45.4	87.6	2220